

Ceramic cutting-off wheel

K 960 TX SPECIAL



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Ceramic Al. oxide
Bond	■■■■■■■■
Aggression	■■■■■■■■
Service life	■■■■■■■■

Product benefit

Free of iron, sulfur and chlorine - Outstanding performance in daily use - Highest cutting performance, even with low grinding pressure - 25 pieces delivered in the Kronenflex® box for long lasting high performance and moisture protection

Application

Steel	●
Stainless steel	●
High alloy steel	●
Carbon steel	●
Titanium	●

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1 x 22,23		80 m/s	13300 rpm	25	328885
125 x 1 x 22,23		80 m/s	12200 rpm	25	328886

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

